

POWERFUL SOLUTIONS WITH CUSTOMER FOCUS

> SMT Africa is a premium distributor and aftersales partner for the equipment and transport industry.

DELIVERY & TRAINING

When purchasing a bus from SMT you benefit from:

- thorough and professional vehicle handover
- driver training and vehicle handling

WARRANTY

For greater peace of mind on your Volvo Bus, warranty of 200 000 km over 2 years:

- year one: full warranty on chassis and body
- year two: warranty on driveline only

AFTERSALES NETWORK

Whatever your business, SMT will help you avoid downtime and unexpected costs by:

- efficient response that gets your equipment back up and running as quickly as possible by our aftersales network
- highly skilled and well trained technical and service teams

LOCATION & CONTACT



All photos in this document are non-contractua

SMT AFRICA

Iouri de Bilderling **BU People Transport Director**



WWW.SMT.NETWORK





PARADISO 1200 B11R 4X2 G8







Torino B8R

Viaggio 1050 B8R

Paradiso 1200 **B11R G8**







Paradiso 1350 **B11R**

Paradiso 1600 LD B11R

Paradiso 1800 DD B11R

B11R 4x2 G8 **370HP ENGINE**

TECHNICAL SPECIFICATIONS

ENGINE

| Туре | Volvo D11A370 |
|---------------------|-----------------------------|
| Maximum power | 370 hp (272 kW) at 1900 rpm |
| Maximum torque | 1770 Nm at 1000-1400 rpm |
| Number of cylinders | 6 |
| Displacement | 10.8 dm ³ |
| Cylinder bore | 123 mm |
| Stroke | 135 mm |

GEARBOX

| hift |
|------|
| |
| |

BRAKE SYSTEM

Disk Brake + EBS built-in hydraulic retarder



DIMENSIONS

| DIMENSION | MM |
|--------------------|---------|
| Overall bus lenght | 13200 |
| Bus width | 2600 |
| Bus height | 3920 |
| Wheelbase | 7040 mm |
| Front overhang | 2600 |
| Rear overhang | 3460 |
| Ground clearance | 390 mm |

| WEIGHT | KG |
|-------------|------------------|
| Curb weight | Aprox. 13 900 kg |
| GVW | 19 500 kg |
| | |

FUEL TANK

| Туре | Plastic fuel tank |
|----------|-------------------|
| Capacity | 500 L |

AXLES

| Front | Volvo RFS | |
|---------------|-------------------|--|
| Rear | Volvo RS1228C | |
| Load capacity | up to 7.5 T front | |
| | 12 T rear | |
| | - | |

TYRES

| Dimension | 295/80R22.5 |
|-----------|-------------|
| RIM | 8.25x22.5 |
| | |

SUSPENSION

| Front | 2 air bellows |
|-------|---------------|
| Rear | 4 Air bellows |

BATTERY

| Voltage | 12 V | | | | |
|---------------------|----------------|--|--|--|--|
| Capacity | 170 Ah, 225 Ah | | | | |
| Number of batteries | 2 | | | | |

BODY

| Luggage capacity | 12m ³ | | |
|------------------|---------------------------------|--|--|
| Material | Galvanized steel and fiberglass | | |
| Dimensions | 13200 x 2600 x 3920 | | |

Volvo: IT'S ALL ABOUT TRUST

> Volvo buses offers a range of city and intercity buses. Fuel efficiency, world-leading hybrid technology, efficient maintenance solutions, renowned safety and outstanding uptime are all Volvo hallmarks.

KEY FEATURES





VOLVO D11A 370 HP ENGINE 6



2X2 WITH TOILET 44 SEATS

| 2 | V 2 14 | /11 | ITO | | | ET | | | | 40 | CE/ | TC | | |
|---|----------|----------|-------|-------|------------|--------|-----|------|----------|-----|-----|-------------|--------|------------|
| | | -900- | -900- | -900- | -750-45 | 0H-740 | 1 | | | | | | 350 | |
| U | <u>R</u> | <u>(</u> | 80 | | <u>(</u> : | Þ | | 26 | <u>R</u> | 136 | | <u>.</u> G. | | IJ |
| | œ | Œ | Œ | | (| 1 | | Æ | 1CE | 170 | 10 | 10 | | Y |
| | | | | | | t U | IJU | | ΠĘ | t.U | | | ∖\⊨ | 6 |
| U | 0771 | 0770 | 0771 | 2000 | 77177 | | | - 07 | | | 770 | 7 | 4301-1 | (C) 11 - 1 |

| 272 11 | | TUJERIJ |
|--------|------------------|---------|
| | 0-+800-+800-+800 | |
| | | |
| | | |



OPTIONAL ITEMS

- 9 USB chargers
- 10 Five screens
- 11 Toilet, fridge + boiler
- 12 4 security cameras with recording system
- ¹³ Snack table on the seats

• The Volvo D11A370 is an in-line six-cylinder 11-liter 370 hp engine which is equipped with an overhead camshaft, four valves per cylinder and common rail injection system. The engine meets the European Union's exhaust emission standards according to Euro 3.