



POWERFUL SOLUTIONS WITH CUSTOMER FOCUS

› SMT Africa is a premium distributor and aftersales partner for the equipment and transport industry.

DELIVERY & TRAINING

When purchasing a truck from SMT you benefit from:

- thorough and professional vehicle handover
- free vehicle training for two drivers

WARRANTY

For greater peace of mind on your Dongfeng truck, warranty of 100 000 km over 2 years:


- year one: warranty on driveline and all other components of the trucks (except tyres and windows)
- year two: warranty on driveline (engine, gearbox, propshaft and axles)

AFTERSALES NETWORK

Whatever your business, SMT will help you avoid downtime and unexpected costs by:

- efficient response that gets your equipment back up and running as quickly as possible by our aftersales network
- highly skilled and well trained technical and service teams

LOCATION & CONTACT



+32 2234 33 00
info.africa@smt.network

WWW.SMT.NETWORK



DONGFENG KL 4x2 315

**LONG-DISTANCE TRANSPORT
AND REGIONAL DISTRIBUTION**



KL 4x2 315



KC 6x4 380
ADR OPTIONAL



KC 6x4 420
ADR OPTIONAL



KC 8x4 375



KC 8x4 420



KC 8x4 420
MINING

KL 4x2

315HP TRACTOR



TECHNICAL SPECIFICATIONS

CAB

Type	Low roof sleeper - 1 bunk
Cab tilting	Hydraulic
Driver's seat	Adjustable
Ventilation	Air conditioning

ENGINE

Type	Cummins L315-30 EURO 2
Maximum power	231 kW (315 Hp) to 2200 rpm/min
Maximum torque	1180Nm at 1400rpm
Number of cylinders	6
Displacement	8,9 L
Cylinder bore	114 mm

GEARBOX

Type	9JS119T-B
Number of gears	9 forward gears and 1 reverse gear, synchronized

CLUTCH

Type	Monodisc
Diameter	430 mm
Operating system	Pneumatic with hydraulic assistance

BRAKE SYSTEM

ABS	
Split pneumatic circuit	
Parking spring brake acting on rear axles	
Exhaust brake	

FUEL TANK

Type	Aluminium tank with lockable cap
Capacity	400 L

AXLES

Front	Elliot type, I - beam section
Rear	Ratio 4.11 Axle and wheel lock
Load capacity	7 T front 13 T rear

TYRES

Dimension	13R22.5
-----------	---------

SUSPENSION

Front	3-leaf springs with shock absorber and stabiliser bar
Rear	4+3-leaf springs with shock absorber and stabiliser bar

BATTERY

Voltage	24 V
Capacity	165x2 A.h

FIFTH WHEEL

Type	2", JSK 35 DVS1-22
Capacity	22 T

DIMENSIONS

DIMENSION	MM	FRAME	MM	WEIGHT	KG
Overall chassis length	5980	Frame width (front)	940	Curb weight	7000
Cab width	2500	Frame width (rear)	800	GCW	20000
Cab height (unladen)	3150	Section height	300	GVW	49000
Wheelbase	3400	Section width	90		
Front overhang	1500	Thickness chassis	8+8		

DONGFENG : IT'S ALL ABOUT TRUST

> Dongfeng Trucks is one of China's leading truck brands and was founded in 1969. In 2015 Dongfeng Motor Group and Volvo Group established a strategic alliance. The company is now expanding rapidly and continues to develop its global sales and service network.

KEY FEATURES



CAB

- 1 Front steel bumper with headlight protection
- 2 Air conditioning
- 3 Sleeper cabin (single bed)

DRIVELINE

- 4 Cummins Engine L315-30 - Euro2
- 5 9 forward and 1 reverse gear

CHASSIS

- 6 Tyres 13R22.5
- 7 7 T and 13 T axles
- 8 Fuel Tank 400 L
- 9 Jost fifth wheel 22 T

4 Cummins L315-30 - EURO 2



- Maximum Power: 231 kW (315 ch) to 2200 rpm/min
- Maximum Torque : 1180Nm at 1400rpm