

V O L V O



Volvo Articulated Haulers 34.5 t / 76,060 lb 35.4 mph 451 hp

A35

Volvo Construction Equipment

A35

Benefit from a host of cutting-edge features designed to boost productivity and maximize uptime.



Productive, efficient and reliable hauling operations.

Take on tough jobs in tough conditions in the Volvo A35, built for exceptional off-road performance, operator comfort, and maximum uptime. With features including Volvo drivetrain with Terrain Memory, an intuitive operator interface, enhanced visibility, superb durability, and lower service costs, the A35 delivers peak productivity, profitability, and performance.



Intuitive in-cab interface

- All essential in-cab information conveniently displayed on just two screens
- Interactive, integrated Volvo Co-Pilot display
- Dynamic instrument cluster in-front of steering wheel



A new level in operator comfort

- Easy access/egress
- Direct field of vision which exceeds industry standards
- Lighting and cameras
- Enhanced storage options
- Easy cleaning
- Range of suspension configurations



Unbeatable off-road performance

- Volvo Automatic Traction control (ATC) with Terrain Memory
- Automatic drive combinations including 6x6 and 6x4
- All-terrain bogie
- Hydro-mechanical steering
- Downhill speed control
- Dynamic and predictive gear selection
- Superior tipping stability



Reduction in service costs

- 250-hour greasing intervals
- 1000-hour engine service intervals
- Industry leading service access
- Remote monitoring and service alerts
- Enhanced electrical service center



Haulers and beyond

- Haul Assist with On-Board Weighing
- Connected Map and Performance Indicator
- Future proofed software architecture
- Connected to Uptime
- Operator Training Program
- Service contracts
- Optimal pass-matching with Volvo loading tools

Intuitive operator interface

Operators can stay in-the-know and focussed on the task at hand thanks to all essential in-cab information conveniently displayed on just two screens. The interactive, integrated Volvo Co-Pilot display offers easy control over essential functions like radio, camera settings, climate control, and machine status. This is combined with the dynamic instrument cluster, positioned in front of the steering wheel, which provides essential vehicle data at a glance.

Volvo Automatic Traction Control with Terrain Memory

Experience superb fuel efficiency without compromising on power and performance thanks to the world-renowned Volvo drivetrain, including Terrain Memory. The intelligent function identifies and remembers slippery road segments to ensure optimized traction control and outstanding off-road mobility.

Enhanced visibility

Visibility is key to a safe, efficient and productive working day and thanks to the redesigned cab panels and wider wiper coverage, operators benefit from a direct field of vision which exceeds industry standards. Work lights activated via the integrated Volvo Co-Pilot are now located on the pillar, providing increased illumination to further optimize visibility.

Haul Assist with On-Board Weighing

Haul Assist, powered by the integrated Volvo Co-Pilot, is a set of tools designed to help you get even more productivity and efficiency from your Volvo Articulated Hauler. A key feature of Haul Assist is On-Board Weighing, which provides real-time payload information which can help to eliminate carry-back and overloading. The result is peak productivity, reduced fuel consumption and less machine wear.



Reduction in service costs

Reduce your service costs thanks to simplified servicing, longer change intervals and easy component access. Benefit from industry leading greasing intervals of 250 hours for maximum uptime, along with Volvo Engine Oil and High Performance Filters which offer 1000 hour engine service intervals.

Unbeatable off-road performance

The A35 delivers unbeatable off-road performance in its class with features including the proven Volvo drivetrain, Automatic Traction Control system with Terrain Memory, automatic drive combinations (including 100% differential locks), all-terrain bogie and hydro-mechanical steering for unmatched traction, stability and precise control.



Volvo A35 in detail

Engine

V-ACT, 13 liter, 6-cylinder straight VGT (Variable Geometry Turbocharged) diesel engine with 4 valves per cylinder, overhead camshaft and electronically controlled unit injectors. It has wet replaceable cylinder liners and replaceable valve guides and valve seats. The engine has cooled EGR (Exhaust Gas Recirculation) and exhaust after treatment with EAT-Muffler (Exhaust After treatment) including DOC (Diesel Oxidation Catalyst), DPF (Diesel Particulate Filter) and SCR (Selective Catalytic Reduction) with an electronically controlled UDS (Urea Dosing System). After treatment system features passive DPF regeneration with an AHI (After treatment Hydro carbon Injection) device as back up.

Engine model	Volvo	D13J
Max power - SAE J1995 Gross	kW (hp)	336 (451)
at engine speed	r/min (r/s)	1,900 (31.7)
Max torque - SAE J1995 Gross	Nm (ft lbf)	2,407 (1,775)
at engine speed	r/min (r/s)	1,100 (18.3)
Displacement	l (in ³)	12.8 (781)

Electrical system

All cables, sockets and pins are identified. Cables are enclosed in plastic conduits and secured to main frame. Prewired for options. Connectors meet IP67 standard for water-proofing as necessary

Voltage	V	24
Battery	V	2 x 12
Battery capacity	Ah	2 x 170
Alternator	kW/A	3.396 / 120
Starter motor	kW	9

Drivetrain

Torque converter with built-in lock-up function.

Transmission: Fully automatic Volvo PowerTronic planetary transmission with nine forward gears and three reverse gears. The transmission has the ability to skip gears for fast and accurate gear selection.

Dropbox: Volvo-developed, in-line design with high ground clearance and 100% longitudinal "dog clutch" type differential lock.

Axles: Heavy duty, purpose built Volvo design with fully floating axle shafts, planetary type hub reductions and 100% dog clutch type diff-lock. Automatic Traction Control system (ATC).

Torque converter		2.1:1
Transmission	Volvo	PT 2529
Dropbox	Volvo	IL2 ATC
Axles	Volvo	ARB H35

Brake system

Fully hydraulic, wet multiple disc brakes with enclosed, forced oil-cooled multiple discs on all wheels. Two circuit brake system. Complies with ISO 3450 at total machine weight.

Circuit division: One circuit for front axle and one for bogie axles.

Parking brake: Spring-applied disc brake on the propeller shaft, designed to hold a loaded machine on a grade of up to 18%. When the parking brake is applied, the longitudinal differential is locked.

Retarder: Service brake retarder function and Volvo Engine Brake (VEB)

Steering System

Hydro-mechanical articulated steering, self compensating design. Two double-acting steering cylinders.

Steering angle: 3,4 steering wheel turns lock-to-lock, $\pm 45^\circ$.

Steering system: including secondary steering fulfills ISO 5010.

Chassis

Frames: box type, heavy duty. High strength steel, robot welded.

Rotating hitch: 100% maintenance free, fully sealed, with permanently greased tapered roller bearings

Cab

Mounted on rubber pads. Ergonomically designed. Unobstructed wide angle forward view. Operator centrally positioned above the front axle. ergonomically positioned controls.

Electronic controlled climate unit with automatic controlled temperature and functionality with high thermal comfort and clean air.

The controls, switches, and instruments in the cab of the hauler machine are designed with a strong focus on ergonomics and the appropriateness of information content for the operator. These elements are strategically placed to provide operators with intuitive access to critical functions while minimizing distractions. Ergonomics play a pivotal role in the design, ensuring that controls are within easy reach and that their layout minimizes operator fatigue during long shifts. The primary 8" display, positioned directly in front of the operator, serves as a central hub for monitoring vital machine functions, displaying information in a clear and organized manner. The 12" secondary display complements this by enhancing situational awareness. The information presented on these displays is carefully curated to deliver the most pertinent data, alerts, and notifications, enabling operators to make informed decisions swiftly and accurately.

Safety: ROPS/FOPS standards approved according to ISO3471, SAE J1040 / ISO3449, SAE J231.

Sound level in cab (ISO 6396) - L _{PA}	dB	72
External sound level (ISO 6395) - L _{WA}	dB	112

Internal sound level with sound kit: 70 dB(A)

External sound level with sound kit: 110 dB(A)



Hydraulic system

Four variable displacement piston pumps driven by the flywheel PTO. Two load-sensing used for steering and tipping and two electrical controlled used for fan, brake cooling and brake power supply. One ground-dependent piston pump for secondary steering mounted on the dropbox. Two return oil filters with magnetic cores provide effective oil filtration

System max working pressure	MPa (psi)	28 (4,061)
-----------------------------	-----------	------------

Dumping System

Patented Load and Dump Brake.

Dumping Cylinders: two single stage double acting cylinders.

Tipping angle	°	71
Tipping time with load	s	12
Lowering time	s	10

Body

Plate thickness

Front	mm (in)	8 (0.31)
Sides	mm (in)	11 (0.43)
Bottom	mm (in)	14 (0.55)
Chute	mm (in)	16 (0.63)

Material	HB450 steel	
----------	-------------	--

Yield strength	N/mm ² (psi)	1,150 (166,793)
----------------	-------------------------	-----------------

Tensile strength	N/mm ² (psi)	1,350 (195,801)
------------------	-------------------------	-----------------

Load Capacity

Standard Body

Load capacity	kg (sh tn)	34,500 (38)
Body, struck	m ³ (yd ³)	16 (20.9)
Body, heaped 2:1	m ³ (yd ³)	21.3 (27.9)

With overhung tailgate

Body, struck	m ³ (yd ³)	16.2 (21.2)
Body, heaped 2:1	m ³ (yd ³)	22 (28.8)

Suspension

Front suspension: Three point suspension consisting of a stay fitted to the frame structure by a spherical rubber bushing, shock absorbers with accumulators and cross stays.

Rear suspension: 3-point bogie beam suspension consisting of a straddle-mounted bogie beam with maintenance free rubber bearings, flexible rubber pads, cross stays and a stay



Specifications

REFILL CAPACITIES				
			A35J	
Crankcase	l	gal	50	13.2
Fuel tank	l	gal	563	148.7
Cooling system	l	gal	44	11.6
Brake cooling system	l	gal	207	54.7
Transmission	l	gal	43	11.4
Dropbox	l	gal	9	2.38
Axles, front/bogie	l	gal	22/51	5.8/13.5
Hydraulic tank	l	gal	199	52.6
DEF	l	gal	53	14.0

SPEED				
			A35J	
Forward				
1	km/h	mph	5.9	3.67
2	km/h	mph	8.6	5.34
3	km/h	mph	10.5	6.52
4	km/h	mph	15.2	9.44
5	km/h	mph	21.9	13.6
6	km/h	mph	27.7	17.2
7	km/h	mph	36.6	22.7
8	km/h	mph	48.5	30.1
9	km/h	mph	57	35.4
Reverse				
1	km/h	mph	6.6	4.1
2	km/h	mph	9.5	5.9
3	km/h	mph	18	11.2

OPERATING WEIGHT UNLOADED				
			A35J	
Tires			26.5R25*	
Front	kg	lb	16,430	36,222
Rear	kg	lb	13,470	29,696
Total	kg	lb	29,900	65,918
Payload	kg	lb	34,500	76,059





Operating weight includes all fluids and operator

*) A35J with tires 775/65R29, add 200 kg (440 lb)/axle

TOTAL WEIGHT				
			A35J	
Tires			26.5R25*	
Front	kg	lb	20,430	45,040
Rear	kg	lb	43,940	96,871
Total	kg	lb	64,370	141,912

*) A35J with tires 775/65R29, add 200 kg (440 lb)/axle

GROUND PRESSURE						
			A35J			
Tires			26.5R25		775/65R29	
Unloaded						
Front	kPa	psi	138	20	117	17
Rear	kPa	psi	56	8	49	7
Loaded						
Front	kPa	psi	171	25	146	21
Rear	kPa	psi	184	27	157	23



DIMENSIONS				
Pos	Unit		A35J	
A	mm	ft in	11,261	36'11"
A ₁	mm	ft in	5,459	17'11"
A ₂	mm	ft in	6,418	21'1"
B	mm	ft in	5,811	19'1"
C	mm	ft in	3,568	11'8"
C ₁	mm	ft in	1,819	6'0"
D	mm	ft in	3,084	10'1"
D ₁	mm	ft in	2,941	9'8"
E	mm	ft in	1,277	4'2"
F	mm	ft in	4,628	15'2"
G	mm	ft in	1,940	6'4"
H	mm	ft in	1,609	5'3"
I	mm	ft in	494	1'7"
J	mm	ft in	2,940	9'8"
K	mm	ft in	2,367	7'9"
L	mm	ft in	855	2'10"
M	mm	ft in	7,340	24'1"
N	mm	ft in	9,118	29'11"
N ₁	mm	ft in	4,429	14'6"
O	mm	ft in	3,218	10'7"

DIMENSIONS				
Pos	Unit		A35J	
P	mm	ft in	3,028	9'11"
Q	mm	ft in	2,801	9'2"
R	mm	ft in	586	1'11"
R ₁	mm	ft in	677	2'7"
S	mm	ft in	2,651	8'8"
T	mm	ft in	3,401	11'2"
U	mm	ft in	3,516	11'6"
V	mm	ft in	2,690	8'10"
W	mm	ft in	3,345	11'0"
X	mm	ft in	522	1'8"
X ₁	mm	ft in	607	2'0"
X ₂	mm	ft in	758	2'6"
Y	mm	ft in	2,690	8'10"
Z	mm	ft in	3,345	11'0"
a ₁	°		23.8	
a ₂	°		71	
a ₃	°		45	

A35J: Unloaded machine with 26.5R25

Equipment

STANDARD EQUIPMENT

Cab/Operator environment

Operator seat with head restraint (air suspended and heated)
Electronic Climate Control
Cup holder / storage tray
Cell phone holder
Instructor seat with seat belt
Overhead console for CC Radio, Tachograph, etc.
Air suspended / heated operator seat
Sliding window
Cooled / Heated storage box
Front sun visor
Tilt/telescopic steering wheel
Loud speakers (4)
Dynamic instrument cluster and integrated Co-Pilot
Automatic pre-start checks
Troubleshooting diagnostics

Engine

Preheater for easier cold starts
VEB (exhaust retarder EPG + compression brake)

Wheels and tires

26.5R25

Electric powertrain

6x4 and 6x6 Automatic Traction Control (ATC)
Dog clutch type 100% diff-locks in all axles
Cruise Control
Dropbox with longitudinal diff-lock
Torque converter with automatic lock-up in all gears

Electrical system

Battery disconnect switch
Electrical Interface
Charging studs
Power outlets
USB-C 2.0 (2)
USB-A 3.0 (1)
24V (2)
Exterior and Interior lights (all LED)

Brake system

Two circuit, fully hydraulic, wet discs on all axles (externally cooled)
Down Hill Speed Control
Hill assist
Load & Dump Brake
Retarder pedal
Parking brake on propeller shaft

STANDARD EQUIPMENT

Dumping System

Body prepared for exhaust heating and optional equipment

Safety

Anti-slip steps and platforms with handrails
Dump body lock
Steering joint lock
Harness anchor points
Rear-view mirrors
Retractable 3-inch 2-point safety belt
ROPS / FOPS protected Care Cab
Secondary steering
Dump support system
Positioning indicators (front and rear)
Entrance camera

Service and Maintenance

Grouped service points and filters
Electrical fuel priming pump
Prepared for fast fueling equipment
Ambient and service lights (LED)
Electrical engine hood
Belly plate with integrated service hatches
Drainage hoses
Tool box
Front service ladder

OPTIONAL EQUIPMENT
Engine
Air filter, heavy duty
Engine heater, electric
Engine heater, diesel
Engine shutdown timer
External emergency engine stop
Operator Environment
Noise reduction kit (fulfils 2000/14/EC)
Anchorage, operator's manual
Cab heating / ventilation timer
Cable kit, for cab heater
Cab air filter (Asbestos dust protection)
Cab air filter (Carbon)
Rear view mirrors, adjustable, el.heated
Sun blinds, side windows
Universal key
Premium operator seat with head restraint (air suspended, cooled / heated), 2-point belt
Premium operator seat with head restraint (air suspended, cooled / heated), 3-point belt
Armrest for operator seat
Hands-free microphone
Radio AM / FM / DAB
Wheels and tires
775/65R29
Drivetrain
Long haul kit, dropbox cooling
Speed limiter (25/30 km/h (15/19 mph))
Electrical system
Warning beacon, LED
Seatbelt indicator, external
Working lights front and rear, LED
Rear view camera
Front view camera
Reverse alarm
Tire Pressure Monitoring System

OPTIONAL EQUIPMENT
Suspension
Rubber front suspension
Hydraulic front suspension
Dumping System
Body exhaust heating
Front spillguard, extra
Side extension, 200 mm (7.9 in)
Side extension, light material
Tailgate, overhung, wire-operated
Tailgate, overhung, linkage-operated
Tailgate, underhung
Wear plates, 450 HB
Wear plates heavy duty, 450 HB
Safety and security
Fire suppression system
Warning triangle
Fire extinguisher, external
Wheel chocks
Service and maintenance
Auto Lube system
Centralized greasing
Tool kit
Other
Arctic oil kit
Fast fuelling system
Jump start connector, ISO-type

V O L V O